Master of the wet-look shine

Maintaining a wet-look shine on your finished floors gives your facility an upscale look that impresses both visitors and guests and takes your image to another level. The Clarke® Ultra Speed Pro® 1500 Floor Burnisher is the affordable, easy-to-use master of the wet-look shine.

Fast. Affordable. Wet-Look Shine.

Powered by a 1,500 rpm motor and built with all-metal materials, the Clarke® Ultra Speed Pro® 1500 Floor Burnisher will give you years of dependable service. And it's as safe and easy to use as it is durable, with fingertip controls, handle-mounted safety switch and circuit breaker, and a 50-foot safety-yellow cord.

Keep your facility looking its impressive best with this easy-to-use, affordable floor burnisher.

- 20-inch path powered by 1,500-rpm motor covers even large areas fast
- · Fingertip controls ensure easy operation
- Handle-mounted, safety lockout switch and circuit breaker help keep operators safe
- All-metal construction, including cast-aluminum chassis, ensure durability



Picture shown may not represent model quoted

Standard equipment

Model ULTRASPEED
1500DC
BURNISHER

Ref. no. 01540A

PRODUCT FEATURES

Folding handle	•
Electric start	•
Direct drive	•
Low noise level	•
Safety Yellow Cord	•
Hospital Grade Plug	•
Flexible Shroud and Felt Dust Seal	•
Self-regulating pad pressure	•
Safety Start Push Button	•
Super Flex Power Cable	•
Motor Carbon Brush Wear Indicator	•
Quick Release Cord Wrap	•
Non-marking Wheels	•
Flexible Pad Driver	•



ULTRASPEED

Master of the wet-look shine

Technical specifications	1500DC BURNISHER
Cable length (M)/ plug type	75 ft/ super flex with hospital-grade plug
Motor type	1.5 HP DC permanent magnet with integrated brush wear indicator
Voltage (V)	120 V
Frequency (HZ)	50/60 Hz
Dust control	Passive dual air port filter bag collection
Sound level	66 dB A
Pad speed (RPM)	1,500 RPM
Weight (lbs)	79 lb
Storage dimensions - height	42 in
Storage dimensions - length	24 in
Storage dimensions - width	16 in
Warranty	Polydur Body - 8 Years, Parts - 3 years, Labor - 2 Years
Operator control handle	Ergonomic dihedral design made of die cast aluminum with molded rubber grips
Main frame	Polydur molded frame
Motor cover	Chrome-plated steel
Handle positions	3 positions – locks upright, locked folded over motor, floats in operation
Handle Latch	Foot pedal release
Wheels	5 in non-marking
Agency approval	cETLus
Pad diameter	20 in

 \bullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	ULTRASPEED 1500DC BURNISHER
Pad 20" / 508 mm				
	PAD-NATURAL-20-5/CS	976327	0	0
	PAD-TAN-20-5/CS	976352	0	0
Passive Dust Collection				
	BAG DUST 10-PACK	54195A	0	0

